



HA LIFTING CAPACITIES · TRAGFÄHIGKEITEN · CAPACITÉS DE LEVAGE · PORTATE · CAPACIDADES DE CARGA

160 t

360°

DIN/ISO

Radius · Ausladung		Main boom · Hauptausleger · Flèche principale · Braccio base · Pluma principal													Radius · Ausladung	
Portée															Portée	
Sbraccio															Sbraccio	
Radio	m	14,7 ¹⁾	14,7	19,3 ¹⁾	19,3	24,0 ¹⁾	24,0	28,6	33,2	37,9	42,5	47,2	51,8	56,0	Radio	
m	t	t	t	t	t	t	t	t	t	t	t	t	t	t	m	
3	500,0*	257,0	-	-	-	-	-	-	-	-	-	-	-	-	3	
3,5	381,0*	257,0	257,0	257,0	-	-	-	-	-	-	-	-	-	-	3,5	
4	346,0*	257,0	257,0	257,0	245,0	245,0	-	-	-	-	-	-	-	-	4	
4,5	317,0*	257,0	257,0	257,0	245,0	245,0	-	-	-	-	-	-	-	-	4,5	
5	293,0*	253,0	257,0	252,0	245,0	245,0	210,0	-	-	-	-	-	-	-	5	
6	257,0	224,0	249,0	224,0	233,0	224,0	196,0	166,0	-	-	-	-	-	-	6	
7	231,0	201,0	221,0	201,0	211,0	201,0	184,0	156,0	142,0	-	-	-	-	-	7	
8	207,0	182,0	198,0	182,0	191,0	182,0	171,0	146,0	134,0	117,0	-	-	-	-	8	
9	184,0	166,0	180,0	166,0	174,0	166,0	160,0	138,0	125,0	110,0	95,3	82,9	-	-	9	
10	165,0	153,0	165,0	153,0	159,0	152,0	149,0	130,0	118,0	104,0	89,9	78,6	66,8	-	10	
12	137,0	131,0	136,0	131,0	134,0	130,0	129,0	115,0	103,0	93,5	80,4	71,0	61,2	-	12	
14	-	-	115,0	112,0	115,0	111,0	111,0	102,0	91,1	84,1	72,5	64,4	56,0	-	14	
16	-	-	99,5	97,2	99,7	95,9	96,8	90,5	80,9	75,8	65,9	58,7	51,2	-	16	
18	-	-	75,9	77,5	87,3	83,9	84,8	80,5	72,8	68,5	60,2	53,7	46,9	-	18	
20	-	-	-	-	77,4	74,2	75,1	72,5	66,1	62,1	55,1	49,4	43,1	-	20	
22	-	-	-	-	64,3	64,4	67,1	66,2	60,2	56,5	50,7	45,5	39,7	-	22	
24	-	-	-	-	-	-	59,9	61,0	55,0	51,6	46,7	42,1	36,7	-	24	
26	-	-	-	-	-	-	53,3	54,6	50,3	47,3	43,2	39,1	34,1	-	26	
28	-	-	-	-	-	-	-	49,1	46,2	43,6	40,2	36,4	31,8	-	28	
30	-	-	-	-	-	-	-	44,4	42,5	40,4	37,6	34,0	29,8	-	30	
32	-	-	-	-	-	-	-	-	39,4	37,8	35,4	32,0	28,1	-	32	
34	-	-	-	-	-	-	-	-	36,0	35,2	33,3	30,0	26,3	-	34	
36	-	-	-	-	-	-	-	-	-	32,9	31,6	28,5	24,8	-	36	
38	-	-	-	-	-	-	-	-	-	30,3	29,8	26,9	23,3	-	38	
40	-	-	-	-	-	-	-	-	-	28,0	28,2	25,6	22,1	-	40	
42	-	-	-	-	-	-	-	-	-	-	26,3	24,3	20,8	-	42	
44	-	-	-	-	-	-	-	-	-	-	24,5	23,1	19,8	-	44	
46	-	-	-	-	-	-	-	-	-	-	-	22,0	18,7	-	46	
48	-	-	-	-	-	-	-	-	-	-	-	20,9	17,8	-	48	
50	-	-	-	-	-	-	-	-	-	-	-	-	17,0	-	50	
52	-	-	-	-	-	-	-	-	-	-	-	-	16,2	-	52	

Remarks · Bemerkungen · Remarques · Osservazioni · Observaciones

- 1) 180 t counterweight, additional central outriggers, double hook block required
180 t Gegengewicht, Zusatzabstützung, Doppelunterflasche erforderlich
180 t contrepoids, calage centrale, crochet-moufle double nécessaire
180 t contrappeso, stabilizzatori supplementari, doppio gancio richiesto
180 t de contrapeso, apoyos centrales adicionales, gancho doble

* over rear · nach hinten · sur l'arrière · sul retro · hacia atrás