



19.2t 平衡重 全伸支腿 360° 作业 19.2t counterweight, 360° swing on full-extended outriggers									
幅度 Working radius (m)	主臂长度(m) boom length								
	12.8	17.2	21.6	26	30.4	34.8	39.2	43.6	48
3	100	80							
4	88	70	61						
5	70	61	54.3	42	40				
6	57	54	48.7	42	36.5	31.1			
7	47	47.5	44.1	38.6	33.5	29	24.5		
8	40.5	40	40.2	35.3	31.1	27.2	23.3	19.3	
9	34.5	35	35	32.3	28.7	25.4	21.8	18.4	14
10	30	30	30	29.9	26.6	23.6	20.6	17.5	13.4
12		23	22.8	24.1	23.3	20.9	18.5	15.7	11.6
14		16.6	16.4	17.7	18.6	18.5	16.4	14.2	11.3
16			12.2	13.4	14.2	14.9	14.9	13	10.1
18			9.2	10.4	11.2	11.8	12.3	11.6	9.2
20				8.1	8.9	9.5	10	10.2	8.3
22				6.3	7.1	7.7	8.2	8.4	7.7
24					5.7	6.2	6.8	7.0	7.1
26					4.5	5.1	5.7	5.8	6.1
28						4.6	4.7	4.8	5.1
30						3.3	3.9	4.0	4.2
32							3.2	3.3	3.5
34							2.5	2.7	2.9
36								2.1	2.4
38								1.6	1.9
39									1.5
40									1.1
42									
倍率 Parts of line	12	10	8	6	5	4	4	3	2
最小主臂仰角 (°) Min. boom angle	20	22	23	24	25	25	26	26	26
最大主臂仰角 (°) Max. boom angle	71	77	77	78	80	81	81	81	81
使用吊钩 hook block	100吨吊钩(1017kg) hook block for 100t			50吨吊钩(418kg) hook block for 50t					